



**SURE SEAL® IMPREGNATOR FOR PORCELAIN AEROSOL  
(Tiler's Choice)  
TECHNICAL DATA SHEET**



**Benefits and Characteristics**

- Low odour aerosol formulation
- Will not alter coefficient of friction
- Slower drying; easy to work with
- Helps prevent permanent staining from oil and water-based stains
- Blocks moisture penetration that causes mildew
- Preserves and protects without discoloration
- Resists UV degradation
- Use on polished and unpolished surfaces
- Allows treated surfaces to breathe

**Product Description:** Unique, low-odour impregnator/sealer aerosol formulation for use on both interior and exterior tile and masonry surfaces. Specifically formulated for polished surfaces such as porcelain, granite and marble, but is also excellent for use on sandstone, pavers and terracotta tiles.

**Directions for Application on Polished Porcelain, Marble or Granite:** Test in obscure area to determine suitability for the intended use. Surface should be clean, dry and free from any waxes, coatings, grout residue or finishes. The use of Sure Clean Porcelain cleaner is highly recommended for this purpose. Protect any painted or stained surface adjacent to the application area. Apply one good coat to the surface and grout lines by holding can approximately 15-20cm away from desired surface and spray slowly in a sweeping motion. For best results, leave to dry for a minimum of 1 hour, then re-apply a second coat to the area. Buff treated area (swiftly) before the second coat is dry using a rag or a woollen soft pad. For optimum results, avoid use of treated area for at least 5 hours (to allow for curing). Sure Seal® should only be used in open or well-ventilated areas, or when a suitable mask is worn.

**General Application Instructions for Grout, Tile or Masonry Products:** Test in obscure area to determine suitability for the intended use. Surface should be clean, dry and free from any waxes, coatings or finishes. Protect any painted or stained surface adjacent to application area. Apply one good coat to the surface and grout lines by holding can approximately 15-20cm away from desired surface and spray slowly in a sweeping motion. For best results, leave to dry for a minimum of 1 hour, then re-apply a second coat to the area. For optimum results, avoid use of treated area for at least 5 hours (to allow for curing). Sure Seal® should only be used in open or well-ventilated areas, or when a suitable mask is worn.



**Pre-Grout Sealer/Grout Release:** Sure Seal® can be used as a grout release prior to grouting to prevent grout stains and facilitate grout cleanup.

**Maintenance:** To clean treated areas, simply use water and mild detergent. There is no need to use harsh cleaning agents such as abrasive powders, ammonia, acids or bleach.

**Coverage:** Seals up to 550 linear metres depending on size of grout joint, or seals up to 20 square metres of tile and grout.

**Quantities:** Available in 300gram Aerosol cans, 12 cans to a carton.

**Technical Data:**

Physical Description

& colour: Aerosol; fine clear spray  
Odour: Paraffinic  
Volatiles: 90% (EC/1999/13)  
Ingredients: Hydrocarbon liquid; propane; butane; other ingredients determined not to be hazardous.

**First Aid and Safety Directions:**

For advice, contact a Poisons Information Centre, phone Australia 131 126 or a doctor. If swallowed, DO NOT induce vomiting. May cause irritation by skin contact. If skin contact, remove contaminated clothing and flush exposed area with water and follow by washing with soap if available. If contact with eyes, immediately flush the eyes with lukewarm, gently flowing water for 20 minutes holding the eyelids open. Obtain medical attention.

Highly flammable. Keep out of reach of children. Avoid breathing of vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Avoid contact with skin, eyes and clothing. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.

**Personal Protective Clothing:** None should be necessary under normal circumstances. For exposure controls in confined spaces, or if excessive or prolonged use is required, see Material Safety Data Sheet for further instructions.

**Transport Information:**

ADG Code: 1950, AEROSOLS  
Hazchem Code: 2Y[E]  
Class: 2  
Packing Group: N/A



**Storage and Disposal:** Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even when empty. Dispose of by putting in garbage or leaving at an appropriate metal recycling collection point. Do not empty into drains.

**Note:** Consult the Sure Seal® Impregnator for Porcelain (Tiler's Choice) aerosol Material Safety Data Sheet for details on safe handling and storage

Manufactured by:  
Sure Seal Sealants Australia Pty. Ltd.  
Suites 3 and 4, 11-15 Leicester Avenue  
Glen Waverley, VIC 3150  
Telephone: +61 (0) 3 9561-8899  
Fax: +61 (0) 3 9561-8944  
Email: [info@suresealsealants.com.au](mailto:info@suresealsealants.com.au)  
Australian website: [www.suresealsealants.com.au](http://www.suresealsealants.com.au)  
International website: [www.seal-guard.eu](http://www.seal-guard.eu)